



Mini Series
Branch Office/Quiet

R-Series
Cost Optimized

H-Series
Power Optimized

M-Series
Capacity Optimized

F-Series
Performance Optimized

High Availability	No	No	Optional	Optional	Optional
Target Use Case	Small Business, Edge, Home	Multi Purpose	Edge, Small and Medium Enterprise	Mission Critical Enterprise	Media Production, Analytics, Virtualization
Form Factor	Mini Tower or 2U Rackmount	1U - 12U Rackmount	2U - 6U Rackmount	4U - 52U Rackmount	2U - 14U Rackmount
Chassis Depth	Mini R: 21", 531 mm	26-39", 660-990 mm	27", 686 mm	27", 686 mm	27", 686 mm
Storage Architecture	Hybrid HDD / SSD or All-Flash	Hybrid HDD / SSD or All-Flash	Hybrid HDD / SSD or All-NVMe Flash	Hybrid HDD / SSD or All-Flash	All-NVMe Flash
Storage	SATA	SATA / SAS	SAS, NVMe	SAS	NVMe, Optional SAS
Write Cache	SATA SSD	SATA SSD, NVMe Option	NVMe	SAS, NVMe, NVDIMM	Distributed Write Log
Read Cache Size	480 GB	12.8 TB NVMe	Up to 12.8 TB NVMe	Up to 12.8 TB NVMe	512 GB DRAM
Cores per Controller	4 - 8	6 - 16	4 - 20	8 - 32	32 - 48
vCPU per Controller	4 - 8	12 - 32	8 - 40	8 - 64	64 - 96
RAM per Controller	16 - 64 GB	32 - 192 GB	64 - 256 GB	96 GB - 768 GB	512 GB
Expansion Shelves	0	2	1	Up to 12	Up to 6
Max Capacity	264 TB	Up to 5 PB	Up to 2.5 PB	Up to 30 PB	Up to 10 PB
Max Effective Capacity*	528 TB	Up to 10 PB	Up to 5 PB	Up to 50 PB	Up to 20 PB
Bandwidth Fibre	1 to 20 Gbit/s	1 to 200 Gbit/s	1 to 200 Gbit/s	1 to 200 Gbit/s	200 - 400 Gbit/s
Channel (option)	Not Available	4x 16 Gbps	2 x 32 Gbps	Up to 4x 32 Gbps	Up to 4 x 32 Gbps
Enterprise File System	OpenZFS - File, Block, and Object Services - Open Source				
Data Management	Unlimited Snapshots, Pool checkpoints, Space-efficient Clones, Replication: Remote, Local, Auto-Resume to Linux ZFS				
Data Reduction	Thin/Thick Provisioning, In-line Adaptive Compression, Clones, Deduplication, Trim				
Access Protocols	SMB 2/3, NFSv3/v4, rsync, SMB Multi-channel, NFSv4, iSCSI, Fibre Channel, VAAI, S3, Distributed Minio, Cloud Sync, HTTP / WebDAV, FTP				
Administration	IPMI, WebUI, REST API, SSH, SNMP, Syslog, LDAP, Kerberos, Active Directory, WebSockets API				

*Maximum effective capacity assumes typical data reduction through compression and deduplication.

Support Options

	Mini Series	R-Series	H-Series	M-Series	F-Series
Hardware Warranty	1 Year	3 Years	Up to 6 Years, Worldwide, Advanced/On-Site Parts Replacement		
Software Support	Email	Worldwide, up to 24 x 365, Phone or Email			
Support Portal	Community Forums	TrueNAS Enterprise Support Portal			
Deployment Services	Self-Deployment		Included Remote Deployment, Performance Tuning, Proactive Monitoring Option		
Software Updates	Included		Included - Zero downtime upgrades with High Availability		

STYLITE



Optimieren Sie Ihre Speicherinfrastruktur mit **TrueNAS**.

Nehmen Sie Kontakt zu uns auf um mehr
zu erfahren.



+49 6131 327020



info@stylite.de



www.stylite.de

